



Meet 10-U2/U3

USB PTZ Camera for Middle and Small Meeting Room

To Make Collaboration Easy and Affordable

Meet 10-U2/U3 is ideal used for video conferencing in the middle and small meeting room. It is equipped with Panasonic's advanced sensor, 10x optical zoom lens, to output crystal clear image with realistic color, even in low light or high contrast of brightness and darkness environment. It works with any of your favorite conferencing software, totally plug and play, use-friendly.



10X

62.5°FOV

USB2.0/3.0

1080P30

Feature and Benefits:

High-definition image

With Panasonic 5MP sensor, to deliver sharp and high-definition image with realistic color; Support WDR, backlight compensation, noise reduction, to adjust image for different working environment

Plug and play

USB3.0 or USB2.0 video output 1080p30 resolution, plug and play, work with any of your favorite video conferencing software.

VISCA control is supported

Support RS232 and RS485 control for different control application and other devices connection, 128 presets adjustable for VISCA control.

10x optical zoom

Uses truly 10x optical zoom lens, with 62.5-degree wide angle FOV, fast and accurate focus performance to capture details in large and middle room.

Easy operation

Matched with IR remote controller, to control PTZ movement, 10 presets and adjust functions as preference in the OSD menu.

Smooth and quite PTZ movement

Smart, compact and decent mechanism, to bring smooth, silent and accurate PTZ movement, to make sure everyone is participated in the meeting.

Compatible With



Used For



Product SPEC

Camera		Meet 10-U3	Meet 10-U2
Item Number	TLC-1000-U3-10		
Sensor	1/2.8-inch high-quality 5MP HD CMOS sensor		
Video System	USB3.0: 1920*1080p30/25; 1280*720p60/50/30/25; 1024*768p30; 800*600p30; 1024*576p30; 960*540p30; 576*448p30; 768*448p30; USB2.0: 1280*720p25,800*600p30;1024*576p30; 960*540p30; 576*448p30;768*448p30; 640*360p30; 512*288p30;		1920x1080P30; 1280x720P30; 640x480P30;
Video Format	YUY2	MJPG	
Lens Zoom	10x optical zoom, 12x digital zoom		
Focal length	f=4.7(wide)~47mm(Tele), F1.6~F3.0		
View Angle	62.5° (wide)~ 6.43° (Tele)		
Vertical viewing angle	40.1° ~ 4.1°		
Diagonal viewing angle	69.7° ~ 7.56°		
Minimum Object Distance	Wide: 0.5m; Tele: 1m		
SNR	>50dB		
Image parameter			
Noise Reduction	2D/3D		
Minimum LUX	0.7lux (50 IRE Max AGC,1/30,F1.8)		
White Balance	Auto/Manual/Indoor/Outdoor/Push/Sodium/Fluorescent		
Focus	Auto / Manual		
Iris	Auto / Manual		
Electronic Shutter	Auto / Manual		
BLC	Supported		
Mechanism			
Pan Rotation Angle	-170° ~ +170°		
Tilt Rotation Angle	-30° ~ +90°		
Pan Rotation Speed	0°~120°/s		
Tilt Rotation Speed	0°~80°/s		
Preset	128 presets via RS232, 10 presets via remote controller		
Control	RS232/RS485/USB/Remote Controller		
Video Port:	USB3.0		
General			
Input voltage	DC12V		
Operating Temperature	-10°C~ 50°C		
Operating Humidity	≤80%		
Color	Silver		
Camera Dimension	148mm×132mm×161mm		
Package Dimension	28x24x24cm		
Package Content	Camera, Remote Controller, RS232 cable, USB2.0/3.0 cable, Power Supply		



Back of Meet 10-U2



Back of Meet 10-U3

