



Meet 12-U2/U3

USB PTZ Camera for Large or Middle Meeting Room

To Make Collaboration Easy and Affordable

Meet 12-U2/U3 is ideal used for video conferencing in the large and middle meeting room. It is equipped with Panasonic's advanced sensor, 12x optical zoom lens, to output crystal clear image with realistic color, even in low light or high contrast of brightness and darkness environment. It works with any of your favorite conferencing software, totally plug and play, use-friendly.



12X

72.5°FOV

USB2.0/3.0

1080P30

Features and Specification

High-definition image

With Panasonic 5MP sensor, to deliver sharp and high-definition image with realistic color; Support WDR, backlight compensation, noise reduction, to adjust image for different working environment.

Plug and play

USB3.0 or USB2.0 video output 1080p30 resolution, plug and play, work with any of your favorite video conferencing software.

VISCA control is supported

Support RS232 and RS485 control for different control application and other devices connection, 128 presets adjustable for VISCA control.

12x optical zoom

Uses truly 12x optical zoom lens, with 72.5-degree wide angle FOV, fast and accurate focus performance to capture details in large and middle room.

Easy operation

Matched with IR remote controller, to control PTZ movement, 10 presets and adjust functions as preference in the OSD menu.


Smooth and quite PTZ movement

Smart, compact and decent mechanism, to bring smooth, silent and accurate PTZ movement, to make sure everyone is participated in the meeting

Compatible With



Used For



Product SPEC

Camera	Meet 12-U3	Meet 12-U2
Item Number	TLC-300-U3-12	TLC-300-U2-12
Sensor	1/2.8-inch high quality 5MP HD CMOS sensor,	
Video System	USB3.0: 1920*1080p30/25; 1280*720p60/50/30/25/15; 1024*768p30; 800*600p30; 1024*576p30;960*540p30; 576*448p30; 768*448p30 USB2.0: 720P25; 640*360@30; 704*576@30; 640*480@30;	1920*1080P30; 1280*720P30;640*480P30;
Video Format	YUV2	MJPG
Lens Zoom	12x optical zoom, 12x digital zoom	
Focal length	f=3.92 ~ 47.32mm, F1.6 ~ F2.8	
View Angle	72.5° (wide)~ 6.3° (Tele)	
Vertical viewing angle	42.72°~3.66°	
Diagonal viewing angle	78.58°~7.42°	
Minimum Object Distance	Wide: 1.0m; Tele: 1.5m	
SNR	>50dB	
Image parameter		
Noise Reduction	2D/3D	
Minimum LUX	0.7lux (50 IRE Max AGC,1/30,F1.8)	
White Balance	Auto/Manual/Indoor/Outdoor/Push/Sodium/Fluorescent	
Focus	Auto / Manual	
Iris	Auto / Manual	
Electronic Shutter	Auto / Manual	
BLC	Supported	
Mechanism		
Pan Rotation Angle	-170° ~ +170°	
Tilt Rotation Angle	-30° ~ +90°	
Pan Rotation Speed	0°~120°/s	
Tilt Rotation Speed	0°~80°/s	
Preset	128 presets via RS232, 10 presets via remote controller	
Control	RS232/RS485/USB/Remote Controller	
Video Port:	USB3.0/USB2.0	
General		
Input voltage	DC12V	
Operating Temperature	-10°C~ 50°C	
Operating Humidity	≤80%	
Color	Silver	
Camera Dimension	220mm×190mm×173mm	
Package Dimension	32x30x31cm	
Package Content	Camera, Remote Controller, RS232 cable, USB2.0/3.0 cable, Power Supply	



Back of Meet 12-U2



Back of Meet 12-U3

